

Specifications		Fx45 $\alpha$	
Operating weight			
Side plate	173 kg		381 lb
T-Box	175 kg		386 lb
ST-Box <sup>1)</sup>	187 kg		412 lb
Height			
Side plate	1,345 mm		53"
T-Box	1,150 mm		45"
ST-Box <sup>1)</sup>	1,138 mm		45"
Impact rate	600 - 1,100 min <sup>-1</sup>		600 - 1,100 bpm
Oil flow rate	30 - 60 l/min		7 - 13 gal/min
Operating oil pressure	12 - 16 MPa		1,740 - 2,321 psi
Rod diameter	60 mm		2.4"
Hose diameter	12 mm		0.47"
Excavator weight	3.0 - 4.5 t		3.3 - 5.0 USt
Sound power level <sup>2)</sup>			
Side plate		126 LWA (dB)	
T-Box		122 LWA (dB)	
ST-Box <sup>1)</sup>		120 LWA (dB)	
Guaranteed sound power level <sup>2)</sup>			
Side plate		127 LWA (dB)	
T-Box		123 LWA (dB)	
ST-Box <sup>1)</sup>		121 LWA (dB)	

1) Sound and vibration damping

2) EN ISO3744:2010



Side plate



T-Box



ST-Box