

Specifications		Fx55 $\alpha$	
Operating weight			
Side plate	220 kg		485 lb
T-Box	245 kg		540 lb
ST-Box <sup>1)</sup>	256 kg		564 lb
Height			
Side plate	1,388 mm		55"
T-Box	1,248 mm		49"
ST-Box <sup>1)</sup>	1,234 mm		49"
Impact rate	500 - 1,100 min <sup>-1</sup>		500 - 1,100 bpm
Oil flow rate	40 - 85 l/min		9 - 19 gal/min
Operating oil pressure	12 - 16 MPa		1,740 - 2,321 psi
Rod diameter	68 mm		2.7"
Hose diameter	12 mm		0.47"
Excavator weight	4.0 - 5.5 t		4.4 - 6.1 USt
Sound power level <sup>2)</sup>			
Side plate		129 LWA (dB)	
T-Box		122 LWA (dB)	
ST-Box <sup>1)</sup>		119 LWA (dB)	
Guaranteed sound power level <sup>2)</sup>			
Side plate		132 LWA (dB)	
T-Box		123 LWA (dB)	
ST-Box <sup>1)</sup>		122 LWA (dB)	

1) Sound and vibration damping

2) EN ISO3744:2010



Side plate



T-Box



ST-Box